



Deep



	Ø 104mm (Φ 90°90)	Ø 140mm (Φ 125°125)	Ø 180mm (Φ 160°160)
Power	7W 9W 11W	11W 15W	15W 20W 23W
Lumen Output	559lm 757lm 993lm	1006lm 1320lm	1254lm 1680lm 1879lm
Beam Angles	90°	90°	90°
Colour Temperature	2700K 3000K 4000K 5000K	2700K 3000K 4000K 5000K	2700K 3000K 4000K 5000K
CRI	82+ 92+	82+ 92+	82+ 92+

Flat



	Ø 104mm (Φ 90°90)	Ø 140mm (Φ 125°125)	Ø 180mm (Φ 160°160)
Power	7W 9W 11W	11W 15W	15W 20W 23W
Lumen Output	559lm 757lm 993lm	1006lm 1320lm	1254lm 1680lm 1879lm
Beam Angles	90°	90°	90°
Colour Temperature	2700K 3000K 4000K 5000K	2700K 3000K 4000K 5000K	2700K 3000K 4000K 5000K
CRI	82+ 92+	82+ 92+	82+ 92+



Deep



Flat

Finishes

UV Textured White

IP 20

3yr Warranty

Dimmable

General Specifications

Material | Powder Coated Aluminium

Lifetime | >60,000h L70

Colour Deviation | SDCM≤3

Different dimming

Excellent thermal management

Driver

Power Factor | >0.90

240V Remote PC Dimmable Driver

Dimming Type | DALI, TRIAC, 1-10V

Notes

- Different wattage can be provided upon request
- Customization for non-standard solutions in terms of light source, color, length and other specifications.



SUN
Downlight

Sun LED downlight adopts high bright SMD light source. The applications range from commercial, retail and hospitality to residential installations.